

*Application No. 10/634,103*AMENDMENTS TO THE CLAIMS

1. (Cancelled)
2. (Previously Presented) A correlated filter device, comprising:  
a compensation stack including a plurality of layers, wherein an optical thickness of at least some of said layers of said compensation stack does not equal an integer multiple of one-quarter of a wavelength of light having a first wavelength corresponding to a first passband of said filter device having a first center wavelength, wherein said filter device further comprises a second passband having a second center wavelength and a third passband having a third center wavelength, wherein said first center wavelength is separated from said second center wavelength by a first amount, and wherein said second center wavelength is separated from said third center wavelength by a second amount that is not equal to said first amount.
3. (Currently Amended) The device of Claim 2[[1]], wherein said optical thickness of a layer comprises a distance equal to a thickness of said layer multiplied by an index of refraction of said layer.
4. (Currently Amended) The device of Claim 2[[1]], wherein said first wavelength is a wavelength of light in a vacuum.
5. (Currently Amended) The device of claim 2[[1]], further comprising:  
an optical cavity.
6. (Previously Presented) The device of Claim 5, further comprising a reflective stack including a plurality of layers, wherein said compensation stack is

*Application No. 10/634,103*

associated with a first reflective surface of said optical cavity, and wherein said compensation stack comprises a second reflective surface of said optical cavity.

7. (Original) The device of Claim 5, wherein said optical cavity has an optical thickness greater than ten of said first wavelengths.

8. (Original) The device of Claim 5, wherein said optical cavity comprises an etalon.

9. (Original) The device of Claim 8, wherein said etalon comprises at least one of a Silicon etalon and a Germanium etalon.

10. (Original) The device of Claim 8, wherein said etalon comprises a Silicon etalon and has a thickness of about 386.5mm.

11. (Currently Amended) The device of Claim 2[[1]], further comprising: a plurality of optical cavities.

12. (Original) The device of Claim 11, wherein at least some of said optical cavities are formed as layers within said compensation stack.

13. (Original) The device of Claim 11, wherein said plurality of optical cavities comprise layers within a filter having an optical thickness at least as great as one-half of said first center wavelength.

*Application No. 10/634,103*

14. (Currently Amended) The device of Claim 2[[1]], wherein said compensation stack comprises high index of refraction layers formed from Germanium and low index of refraction layers formed from Silicon Monoxide.

15. (Currently Amended) The device of Claim 2[[1]], further comprising:  
a bandpass filter.

16. (Cancelled)

17. (Currently Amended) The system of Claim [[16]] 19, wherein said at least a first optical cavity comprises an etalon having an optical thickness greater than about ten times said wavelength of light at said first passband of said system.

18. (Original) The system of Claim 17, wherein said etalon comprises at least one of a Silicon and a Germanium etalon.

19. (Previously Presented) A system for sensing atmospheric trace gases, comprising:

at least a first optical cavity;

a first reflective stack forming a first reflective surface of said optical cavity, said first reflective stack including a plurality of thin film layers, wherein at least one of said thin film layers has an optical thickness that is not equal to one quarter of a wavelength of light at a first passband of said system;

a second reflective stack forming a second reflective surface of said optical cavity, wherein said first reflective stack comprises a compensation stack, wherein passbands of said system are not regularly spaced, and wherein said second reflective stack comprises a bandpass filter.

*Application No. 10/634,103*

20. (Original) The system of Claim 19, wherein said system includes at least six passbands, and wherein each of said six passbands is centered at an absorption line of an atmospheric gas.

21. (Original) The system of Claim 20, wherein said atmospheric gas comprises one of Carbon Monoxide and Carbon Dioxide.

22. (Currently Amended) The system of Claim 19[[16]], wherein said first reflective stack comprises Germanium high index of refraction layers and Silicon Monoxide low index of refraction layers.

23. (Original) The system of Claim 19, further comprising a detector, wherein light having a wavelength within said first passband, a second passband, and a third passband of said system is received at said detector, and wherein said first, second, and third passbands are separated from one another by different amounts.

24. (Cancelled)

25. (Currently Amended) The system of Claim 29[[24]], wherein said plurality of optical cavities comprise thin film layers having an optical thickness of at least one-half a wavelength of said first wavelength.

26. (Currently Amended) The system of Claim 29[[24]], wherein passbands of said system are not regularly spaced.

27. (Currently Amended) The system of Claim 29[[24]], further comprising:

*Application No. 10/634,103*

a substrate, wherein said compensation stack is interconnected to a first surface of said substrate.

28. (Original) The system of Claim 27, further comprising:

a bandpass filter stack, including a plurality of high index of refraction thin film layers and a plurality of low index of refraction thin film layers interconnected to a second surface of said substrate.

29. (Previously Presented) A system for sensing atmospheric trace gases, comprising:

a correlation filter including:

a plurality of thin film layers, wherein said thin film layers include a plurality of high index of refraction layers and a plurality of low index of refraction layers, wherein at least some of said thin film layers have an optical thickness that is not equal to a quarterwave of light having a first wavelength corresponding to a center wavelength of a first passband of said correlation filter; and

a plurality of optical cavities, wherein said system includes at least six passbands, and wherein each of said six passbands is centered at an absorption line of an atmospheric gas.

30. (Original) The system of Claim 29, wherein said atmospheric gas comprises one of Carbon Monoxide and Carbon Dioxide.

31. (Currently Amended) The system of Claim 29[[24]], wherein said high index of refraction layers comprise Germanium and said low index of refraction layers comprise Silicon Monoxide.

*Application No. 10/634,103*

32. (Previously Presented) A system for sensing atmospheric trace gases, comprising:

a correlation filter including:

a plurality of thin film layers, wherein said thin film layers include a plurality of high index of refraction layers and a plurality of low index of refraction layers, wherein at least some of said thin film layers have an optical thickness that is not equal to a quarterwave of light having a first wavelength corresponding to a center wavelength of a first passband of said correlation filter; and

a plurality of optical cavities, further comprising a detector, wherein light having a wavelength within said first passband, a second passband, and a third passband of said system is received at said detector, and wherein said first, second, and third passbands are separated from one another by different amounts.

33. (Withdrawn) A method for selectively filtering light, comprising:  
identifying a spectral response of interest, wherein said spectral response of interest comprises a number of non-linearly spaced spectral lines;

selecting a desired number of said spectral lines for observation; and

forming a correlation filter comprising a compensation stack having a plurality of layers, at least some of which have an optical thickness that is not equal to one-quarter of a wavelength of light corresponding to one of said spectral lines, wherein said filter substantially blocks the passage of light at wavelengths not corresponding to said selected spectral lines, and wherein said filter substantially passes light at wavelengths corresponding to said selected spectral lines.

34. (Withdrawn) The method of Claim 33, further comprising:  
receiving light;

passing said received light through said correlation filter; and

*Application No. 10/634,103*

outputting from said filter light at wavelengths corresponding to said selected spectral lines.

35. (Withdrawn) The method of Claim 34, further comprising:  
simultaneously detecting an intensity of light at each of said wavelengths  
corresponding to said selected spectral lines.

36. (Withdrawn) The method of Claim 34, wherein said step of outputting  
light at wavelengths corresponding to said selected spectral lines comprises outputting  
light at a center wavelength of each of said selected spectral lines.

37. (Withdrawn) The method of Claim 34, wherein said step of outputting  
light at wavelengths corresponding to said selected spectral lines comprises outputting  
light at wavelengths corresponding to a selected position along a line wing of said  
selected spectral lines, wherein information regarding an altitude distribution of an  
atmospheric gas is obtained.

38. (Withdrawn) The method of Claim 33, wherein an optical path of light  
having a first wavelength through said filter is a first distance, and wherein an optical  
path of light having a second wavelength through said filter is a second distance.

39. (Withdrawn) The method of Claim 33, wherein a phase shift of light by  
said filter is non-linear, wherein a spacing between said first wavelength of said first  
passband, a second wavelength of a second passband, and a third wavelength of a third  
passband of said filter are separated from one another by amounts that are at non-integral  
multiples of an amount equal to one-quarter of said first wavelength.

*Application No. 10/634,103*

40. (Withdrawn) The method of Claim 33, wherein said selected number of spectral lines for observation is at least 6.

41. (Withdrawn) The method of Claim 33, wherein said selected number of spectral lines for observation is at least 8.

42. (Withdrawn) The method of claim 34, further comprising, passing said light through a bandpass filter having a passband that includes wavelengths corresponding to said selected number of absorption lines.

43. (Withdrawn) A system for measuring atmospheric trace gas, comprising:  
means for gathering light from within a first field of view;  
means for filtering said gathered light having passbands at wavelengths corresponding to wavelengths of lines of absorption of an atmospheric gas; and  
means for measuring an intensity of said light within said passbands of said means for filtering.

44. (Withdrawn) The system of Claim 43, further comprising:  
means for calculating a concentration of an atmospheric trace gas from an output of said means for measuring an intensity.

45. (New) The system of Claim 32, wherein said plurality of optical cavities comprise thin film layers having an optical thickness of at least one-half a wavelength of said first wavelength.

46. (New) The system of Claim 32, wherein passbands of said system are not regularly spaced.



*Application No. 10/634,103*

47. (New) The system of Claim 32, further comprising:  
a substrate, wherein said compensation stack is interconnected to a first surface of said substrate.

48. (New) The system of Claim 32, further comprising:  
a bandpass filter stack, including a plurality of high index of refraction thin film layers and a plurality of low index of refraction thin film layers interconnected to a second surface of said substrate.

49. (New) The system of Claim 32, wherein each of said first, second and third passbands is centered at an absorption line of an atmospheric gas.

50. (New) The system of Claim 49, wherein said atmospheric gas comprises one of Carbon Monoxide and Carbon Dioxide.

51. (New) The system of Claim 32, wherein said high index of refraction layers comprise Germanium and said low index of refraction layers comprise Silicon Monoxide.